
FIG.1






FIG. 3






FIG. 4A




DUAL-MODE CONFIGURATION

FIG. 4B



SINGLE-MODE CONFIGURATION

FIG.5






FIG. 7A

FIG. 7B

FIG. 7B

ML

50

ML

50

ML

50

ML

54




FIG. 9A

FIG. 9B

IN CASE OF PR(1, 1, 0, X)	IN CASE OF PR(1,3,3,1)
TIME t-3 t-2 t-1 t Ph	h TIME t-3 t-2 t-1 t Ph
STATE SLO X 0 0 0 SLO PLO	0=0 STATE SLO 0 0 0 0 SLO PLO=0
SL1 X 1 0 0 SLO PL1	1=0 S L1 0 (1 0) 0 STO PL1=0
SL2 X 0 1 0 SL1	S L2 0 0 1) 0 S L1
SL3 X 1 1 0 SL1 PL3	3=1 SL3 0 1 1 0 ST1 PL3=6
SLO X 0 0 1 SL2 PL4	4=1 SLO(0 0 0) 1 SL2 PL4=1
SL1 X 1 0 1 SL2	S L1 (0 (1 0) 1) S T2
SL2 X 0 1 1 SL3 PL6	6=2 SL2 0 0 1) 1 SL3 PL6=4
SL3 X 1 1 1 SL3 PL7	7=2 SL3 0 1 1 1 ST3 PL7=7
STO X 0 0 0 STO PTO	ro=0 STO 1 0 0 0 SLO PTO=1
ST1 X 1 0 0 STO PT1	1=0 ST1 1 1 0 0 STO PT1=4
ST2 X 0 1 0 ST1	ST2 1 0 1) 0 SL1
ST3 X 1 1 0 ST1 PT3	ST3 1 1 0 ST1 PT3=7
STO X 0 0 1 ST2 PT4	STO 1 0 0 1 SL2 PT4=1
ST1 X 1 0 1 ST2	S T1 (1 0) 1) S T2
ST2 X 0 1 1 ST3 PT6	ST2 1 0 1 1 SL3
ST3 X 1 1 1 ST3 PT7	7=2 ST3 1 1 1 ST3 PT7=8
DUAL MODE	 SINGLE MODE

FIG. 10A




FIG. 11A




FIG. 11B




FIG. 12




FIG. 13A

FIG. 13B

PML(t,0)=min PML(t,2)=min	[PML(t-1,0) [PML(t-1,0)	+	BMLO , BML4 ,	PMT(t-1,0) PMT(t-1,0)			;DLO ;DTO
PML(t, 3) =	PML(t-1, 2)	+	BML6				:DT2
PMT(t, 0) =				PMT(t-1, 1)			;DL1
PMT(t, 1)=min			BML3 ,	PMT(t-1,3)			;DL3
PMT(t.3)=min	[PML(t-1.3)]	+	BML7 .	PMT(t-1,3)	+	BMT7]	;DT3

FIG. 14




FIG. 15






FIG. 16





163

FIG. 18

QI		TED ID EXPECTED IL1) VALUE (ML1)	TED ID EXPECTED (ML2)
MO		TED MO EXPECTED VALUE (ML1)	TED MO EXPECTED VALUE (ML2)
Q		ID EXPECTED VALUE (ML1)	ID EXPECTED VALUE (ML2)
(A) DATA FORMAT	(B) TIMING SIGNAL	(C) ML1 EXPECTED VALUE	(D) ML2 EXPECTED

FIG. 19A




FIG. 19B

